

LED FLORA G45 Bulb



Features:



- FLORA heat sink design
- Ra 97 nearly close to incandescent lighting effect
- 6W equivalent to 40W incandescent bulb
- Dimmable version optional
- 85% energy saving
- 2500K/2700K available
- Switching power supply
- CE and RoHS compliant

Cautions:

- Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Indoor use
- Don't use it in sealed fixture
- Consult competent electricians for technical support

| Part No. | G45 K2F40T6 | G45 K2F40T6 | DG45 K2F40T6 |
|-------------------------------------|-------------|-------------|--------------|
| Watt (W) | 6 | 6 | 6 |
| Comparable Incandescent Wattage (W) | 40 | 40 | 40 |
| CCT (K) | 2500K * | 2700K * | 2700K * |
| Luminous Flux (lm) | 470 | 470 | 470 |
| Energy Efficiency Classes | A+ | A+ | A+ |
| Luminous Efficiency (lm/W) | 80 | 80 | 80 |
| Voltage (V) | AC220-240V | AC220-240V | AC220-240V |
| CRI (Ra) | 97 | 97 | 90 |
| Dimmable | No | No | Yes |
| Socket | E27/B22 | E27/B22 | E27/B22 |
| Beam Angle (deg) | 150 | 150 | 150 |
| Lifetime (hrs) | 25,000 | 25,000 | 25,000 |
| Weight (g) | 66 | 66 | 66 |

Mechanical Drawing



Photometric Diagrams

Note: Data collected from tests while lights maintain stable. And they are subject to change without prior notice. For further information, please contact us by market@civilight.com.

* 3000K / 4000K / 5300K also available

Application:

- Perfect solution for chandeliers & pendant lights
- Home, villa and other residential buildings
- Hotels, restaurants, bars, cafes



Indoor

Bedroom

Hotel

Restaurant